



**Specifications Ledvance LED Panel  
Linear Pendant IndiviLED Dali Sensor  
40W 4800lm - 930 Warm White |  
120x12cm UGR<19- Best Colour  
Rendering**

[View Product](#)

## General Information

|                          |                                                                    |
|--------------------------|--------------------------------------------------------------------|
| SKU                      | 253354                                                             |
| EAN                      | 4099854249228                                                      |
| manufacturer_code        | 4099854249228                                                      |
| Brand                    | Ledvance                                                           |
| Manufacturer Name        | LINEAR INDIVILED DIRECT 1200 DALI SENSOR 1200 P 40W 930 DAVR SN WT |
| Any Lamp all-in warranty | 5 Years                                                            |
| Average Lifetime (h)     | 100000                                                             |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x36               |
| Wattage                     | 40W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 930 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light Colour Options        | Single Color       |

|                        |                               |
|------------------------|-------------------------------|
| Luminous Flux (Lumen)  | 4800lm                        |
| Lumen per watt         | 120                           |
| IP-Rating              | IP20                          |
| Impact Protection (IK) | IK06 - 1 joule                |
| Fixture Connection     | PI [Push-in connector 3-pole] |
| Power factor           | >0.90                         |
| Product Type Category  | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Pendant                        |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | -20 to +50                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x12cm |
| Length (mm)    | 1210     |
| Width (mm)     | 125      |
| Height (mm)    | 43       |

## Why Any-lamp?

## Sensor Information


**Order from the largest lighting specialist in Europe**


**Customised quotation**


 Type of sensor

Light Sensor


**Up to 7 years warranty**


**Easy return process**